



coupling type		APC160A	APC200A	APC250A	APC315A	APC400A	APC500A
T_{KN}	Nm	270	550	1000	2000	3500	6500
T_{Kmax}	Nm	540	1100	2000	4000	7000	13000
n_{max}	min ⁻¹	4800	3900	3200	2500	2000	1600
pilot bore ØD4+D5	mm	20	23	23	35	45	55
Max ØD4	mm	48	55	65	90	100	120
Max ØD5	mm	48	55	65	90	100	120
ØD6	mm	150	185	225	280	335	410
Max ØD7	mm	58	66	83	104	120	140
Max ØD8	mm	58	66	83	104	120	140
ØD14	mm	75	90	110	145	170	200
ØD15	mm	75	90	110	145	170	200
L1	mm	170	224	294	311	355	386
L2	mm	83	110	145	153	175	190
L3	mm	83	110	145	153	175	190
Min L4	mm	73	95	128	130	145	160
Min L5	mm	73	95	128	130	145	160
Max L7	mm	10	15	17	23	30	30
Max L8	mm	10	15	17	23	30	30
LM	mm	85	110	130	155	175	190
S1	mm	4	4	4	5	5	6
F1 / F2x45°		2	2	2	2	2,5	2,5
Ma 1	Nm	20	30	40	80	120	160
Ma 2	Nm	25	45	80	160	240	320
I_{ges}	kgm ²	0,016	0,047	0,113	0,328	0,778	1,965
G_{ges}	kg	7	14	24	42	70	115